

Recommended makes and types of summer tyres

Type 911/912 up to 1968										
Wheel size	Size	RO	Axles	Tyre size	Tread designation	Spec.	Characteristics		Vehicles	
							Dry handling	Wet handling		
15-inch	6Jx15	36	FA/RA	185/70 R15 89V	Michelin XWX ¹⁾	1)	++	++	911, all models up to 1968	
					Fulda Y - 2000	N0	+	++		
15-inch	6Jx15	36	FA/RA	195/65 R15 91V	Pirelli P6000 ²⁾	N1	++	+	911, '65 - '67 models	
					Goodyear Excellence	N0	+	++	911 S, '67 & '68 models	
					Fulda Carat Progresso	N0	+	++	911 L and T, '68 model	
					Dunlop SP Sport FastResponse	N0	++	++	912, '66 - '68 models	
Type 911 as of 1969										
Wheel size	Size	RO	Axles	Tyre size	Tread designation	Spec.	Characteristics		Vehicles	
							Dry handling	Wet handling		
15-inch	6Jx15	36	FA	195/65 R15 94W	Pirelli P 6000 ²⁾	N1	++	+	911, as of '69 model	
	7Jx15	23,3	RA	215/60 R15 94W	Pirelli P 6000 ²⁾	N1	++	+		
16-inch	6Jx16	36	FA	205/55 ZR16	Pirelli P-Zero Direzionale	N3	++	++	911, as of '69 model	
					Bridgestone Potenza S-02	N3	0	++		
					Continental ContiSportContact	N1	+	+++		
					Michelin SX MXX3	N2	++	++		
					Michelin Pilot Exalto PE2	N0	+	+++		
	7Jx16	23,3	RA	205/55 ZR16	Pirelli P-Zero Direzionale	N3	++	++		
					Bridgestone Potenza S-02	N3	0	++		
					Continental ContiSportContact	N1	+	+++		
					Michelin SX MXX3	N2	++	++		
					Michelin Pilot Exalto PE2	N0	+	+++		
	6Jx16	36	FA	205/55 ZR16	Pirelli P-Zero Direzionale	N3	++	++	911, as of '69 model	
					Bridgestone Potenza S-02	N3	++	+		
					Continental ContiSportContact	N1	+	+++		
					Michelin SX MXX3	N2	+	+		
					Michelin Pilot Exalto PE2	N0	+	+++		
7Jx16	23,3	RA	225/50 ZR16	Pirelli P-Zero Asimmetrico	N3	++	++			
				Bridgestone Potenza S-02	N3	++	+			
				Continental ContiSportContact	N1	+	+++			
				Michelin SX MXX3	N2	+	+			
				Michelin Pilot Exalto PE2	N0	+	+++			
Type 911 Turbo (930)										
Wheel size	Size	RO	Axles	Tyre size	Tread designation	Spec.	Characteristics		Vehicles	
							Dry handling	Wet handling		
16-inch	7Jx16	23,3	FA	205/55 ZR16	Pirelli P-Zero Direzionale	N3	++	++	911 Turbo ('75 - '89 models)	
					Bridgestone Potenza S-02	N3	+	++		911 Carrera 'Turbo Look' ('85 - '86 models)
					Continental ContiSportContact	N1	++	+++		
16-inch	8Jx16	10,6	RA	225/50 ZR16	Michelin SX MXX3	N2	+	+		
					Pirelli P-Zero Asimmetrico	N3	++	++		
					Bridgestone Potenza S-02	N3	+	++		
					Continental ContiSportContact	N1	++	+++		
					Michelin SX MXX3	N2	+	+		
16-inch	7Jx16	23,3	FA	205/55 ZR16	Michelin SX MXX3	N2	++	++	911 Turbo ('75 - '89 models)	
					Continental ContiSportContact	N1	+++	+++		911 Carrera 'Turbo Look' ('85 - '86 models)
16-inch	9Jx16	15	RA	245/45 ZR16	Michelin SX MXX3	N2	++	++		
					Continental ContiSportContact	N1	+++	+++		

0 = satisfactory; + = good;
++ = very good; +++ = excellent

Only tyres of the same make and type, with the same speed index and the same specification code (N0, N1, N2 ...) may be used on a vehicle.

Speed index:
V= 240 km/h
W= 270 km/h
(169 mph)

¹⁾ Only one version of this tyre is produced. It therefore has no (!) specification code. However, it still meets all Porsche requirements and is therefore approved accordingly.
This is the only tyre that may also be mounted with a tube.
Mounting tyres with tubes is not permitted for all other tyres.

²⁾ Load index/speed index 91W

Further detailed information about permitted wheel and tyre sizes as well as spacers that may be required can be found in the relevant parts certificates/manufacturer's certificates held by the Porsche partners.

Recommended makes and types of summer tyres

Type 914	up to 1968								
	Size	RO	Axles	Tyre size	Tread designation	Spec.	Characteristics		Vehicles
Wheel size							Dry handling	Wet handling	
15-inch	6Jx15	36	FA/RA	185/70 R15 89V	Michelin XWX ¹⁾	¹⁾	++	++	914, 914/6
					Fulda Y - 2000	N0	+	++	
	6Jx15	36	FA/RA	195/65 R15 91V	Pirelli P 6000 ²⁾	N1	++	+	914
					Goodyear Excellence	N0	+	++	914/6, '70 - '72 models
					Fulda Carat Progresso	N0	+	++	
					Dunlop SP Sport FastResponse	N0	++	++	
	6Jx15	36	FA	195/65 R15 94W	Pirelli P 6000 ²⁾	N1	++	+	914/6, '70 - '72 models
	7Jx15	23,3	RA	215/60 R15 94W	Pirelli P 6000 ²⁾	N1	++	+	

0 = satisfactory; + = good;
++ = very good; +++ = excellent

Only tyres of the same make and type, with the same speed index and the same specification code (N0, N1, N2 ...) may be used on a vehicle.

Speed index:
V= 240 km/h
(150 mph)
W= 270 km/h

¹⁾ Only one version of this tyre is produced. It therefore has no (!) specification code. However, it still meets all Porsche requirements and is therefore approved accordingly.
This is the only tyre that may also be mounted with a tube.
Mounting tyres with tubes is not permitted for all other tyres.

²⁾ Load index/speed index 91W

Further detailed information about permitted wheel and tyre sizes as well as spacers that may be required can be found in the relevant parts certificates/matrix certificates held by the Porsche partners.

Recommended makes and types of summer tyres

Type 924									
	Size	RO	Axles	Tyre size	Tread designation	Spec.	Characteristics		Vehicle
Wheel size							Dry handling	Wet handling	
15-inch	6Jx15	36	FA/RA	185/70 R15 89V	Michelin XWX ¹⁾	1)	++	++	924, '76 - '85 models
					Fulda Y - 2000	N0	+	++	924 S, '86 - '88 models 924 Turbo, '79 - '82 models 924 Carrera GT, '81 model
	7Jx15	23,3	FA/RA	195/65 R15 91V	Pirelli P 6000 ²⁾	N1	++	+	924, '76 - '85 models
					Goodyear Excellence	N0	+	++	924 S, '86 - '88 models
					Fulda Carat Progresso	N0	+	+++	924 Turbo, '79 - '82 models
					Dunlop SP Sport FastResponse	N0	++	++	924 Carrera GT, '81 model
	7Jx15	23,3	FA/RA	215/60 R15 94W	Pirelli P 6000 ²⁾	N1	++	+	924 Turbo, '79 - '82 models 924 Carrera GT, '81 model
16-inch	6Jx16	52,3/ 53	FA/RA	205/55 ZR16	Pirelli P-Zero Direzionale	N3	++	++	924 Turbo, '79 - '82 models
					Bridgestone Potenza S-02	N3	0	++	924 S, '86 - '88 models
	6Jx16	52,3/ 53	FA	205/55 ZR16	Continental ContiSportContact	N1	+	+++	
					Michelin SX MXX3	N2	++	++	
					Michelin Pilot Exalto PE2	N0	+	+++	
					Pirelli P-Zero Direzionale	N3	++	++	924 Turbo, '79 - '82 models
	7Jx16	52,3/ 55	RA	205/55 ZR16	Bridgestone Potenza S-02	N3	0	++	924 S, '86 - '88 models
					Continental ContiSportContact	N1	+	+++	
					Michelin SX MXX3	N2	++	++	
					Michelin Pilot Exalto PE2	N0	+	+++	
	7Jx16	52,3/ 55	RA	205/55 ZR16	Pirelli P-Zero Direzionale	N3	++	++	
					Bridgestone Potenza S-02	N3	0	++	
					Continental ContiSportContact	N1	+	+++	
					Michelin SX MXX3	N2	++	++	
					Michelin Pilot Exalto PE2	N0	+	+++	

0 = satisfactory; + = good;
++ = very good; +++ = excellent

Only tyres of the same make and type, with the same speed index and the same specification code (N0, N1, N2 ...) may be used on a vehicle.

Speed index:
V= 240 km/h
W= 270 km/h
(169 mph)

¹⁾ Only one version of this tyre is produced. It therefore has no (!) specification code. However, it still meets all Porsche requirements and is therefore approved accordingly.

²⁾ Load index/speed index 91W

Further detailed information about permitted wheel and tyre sizes as well as spacers that may be required can be found in the relevant parts certificates/manufacturer's certificates held by the Porsche partners.

Recommended makes and types of summer tyres

Type 928									
Wheel size	Size	RO	Axles	Tyre size	Tread designation	Spec.	Characteristics		Vehicles
							Dry handling	Wet handling	
16-inch	7Jx16	65	FA/RA	225/50 ZR16	Pirelli P-Zero Asimmetrico	N3	++	++	928, '78 - '82 models
					Bridgestone Expedia S-01	N2	0	+	928 S, '80 - '86 models
					Bridgestone Potenza S-02	N3	++	+++	
					Continental ContiSportContact	N1	++	+++	
					Michelin SX MXX3	N2	+	+	
					Michelin Pilot Exalto PE2	N0	0	+++	
	7Jx16	65	FA	225/50 ZR16	Michelin SX MXX3	N2	+++	++	928 GT, up to '92
					Bridgestone Expedia S-01	N2	++	++	928 S4, CS, GT '89
					Bridgestone Potenza S-02	N3	+	+++	
					Continental ContiSportContact	N1	+++	+++	
					Michelin SX MXX3	N2	+++	++	
					Bridgestone Expedia S-01	N2	++	++	
	8Jx16	52,3	RA	245/45 ZR16	Bridgestone Potenza S-02	N3	+	+++	
					Continental ContiSportContact	N1	+++	+++	
					Michelin SX MXX3	N2	+++	++	
					Bridgestone Expedia S-01	N2	++	++	
					Bridgestone Potenza S-02	N3	+	+++	
					Continental ContiSportContact	N1	+++	+++	
17-inch	7.5 Jx17	65	FA	225/45 ZR17	Bridgestone Potenza S-02	N3	+++	+	928 S4, CS, GT '89, GTS
					Michelin PilotSport PS2	N3	++	++	
					Bridgestone Potenza S-02	N3	+++	+	
					Michelin PilotSport PS2	N3	++	++	

0 = satisfactory; + = good;
++ = very good; +++ = excellent

Only tyres of the same make and type, with the same speed index and the same specification code (N0, N1, N2 ...) may be used on a vehicle.

Further detailed information about permitted wheel and tyre sizes as well as spacers that may be required can be found in the relevant parts certificates/manufacturer's certificates held by the Porsche partners.

Recommended makes and types of summer tyres

Type 944									
	Size	RO	Axles	Tyre size	Tread designation	Spec.	Characteristics		Vehicles
							Dry handling	Wet handling	
Wheel size 16-inch	7Jx16	23,3	FA/RA	205/55 ZR16	Pirelli P-Zero Direzionale	N3	++	++	944, '82 - '86 models
					Michelin Pilot Exalto PE2	N0	0	++	
					Bridgestone Potenza S-02	N3	+	+++	
					Continental ContiSportContact	N1	++	++	
					Michelin SX MXX3	N2	+	+++	
	7Jx16	23,3	FA	205/55 ZR16	Pirelli P-Zero Direzionale	N3	++	++	944, '82 - '86 models
					Bridgestone Expedia S-02	N3	++	+	944 Turbo, '85 - '86 models
					Continental ContiSportContact	N1	+	+++	
					Michelin SX MXX3	N2	+	+	
					Michelin Pilot Exalto PE2	N0	+	+++	
	8Jx16	23,3	RA	225/50 ZR16	Pirelli P-Zero Assimetrico	N3	++	++	
					Bridgestone Expedia S-02	N3	++	+	
					Continental ContiSportContact	N1	+	+++	
					Michelin SX MXX3	N2	+	+	
					Michelin Pilot Exalto PE2	N0	+	+++	
	7Jx16	52.3/ 55	FA	205/55 ZR16	Pirelli P-Zero Direzionale	N3	++	++	944, '87 - '89 models
					Bridgestone Expedia S-02	N3	++	+	944 S, '87 - '88 models
					Continental ContiSportContact	N1	+	+++	944 S2, '89 - '91 models
					Michelin SX MXX3	N2	+	+	944 Turbo, '87 - '91 models
					Michelin Pilot Exalto PE2	N0	+	+++	
	8Jx16	52.3/ 52	RA	225/50 ZR16	Pirelli P-Zero Assimetrico	N3	++	++	
					Bridgestone Expedia S-02	N3	++	+	
					Continental ContiSportContact	N1	+	+++	
					Michelin SX MXX3	N2	+	+	
					Michelin Pilot Exalto PE2	N0	+	+++	
	7Jx16	65	FA	225/50 ZR16	Michelin SX MXX3	N2	+++	++	944 Turbo S
					Bridgestone Expedia S-01	N2	++	++	944 S2, R01 chassis
					Bridgestone Potenza S-02	N3	+	+++	
					Continental ContiSportContact	N1	+++	+++	
					Michelin SX MXX3	N2	+++	++	
	9Jx16	60	RA	245/45 ZR16	Bridgestone Expedia S-01	N2	++	++	
					Bridgestone Potenza S-02	N3	+	+++	
					Continental ContiSportContact	N1	+++	+++	
					Michelin SX MXX3	N2	+++	++	
					Continental ContiSportContact	N1	+++	+++	
Wheel size 17-inch	7.5 Jx17	65	FA	225/45 ZR17	Bridgestone Potenza S-02	N3	+++	+	944, '87 - '89 models
					Michelin PilotSport PS2	N3	++	++	944 S, '87 - '88 models
	9Jx17	55	RA	255/40 ZR17	Bridgestone Potenza S-02	N3	+++	+	944 S2, '89 - '91 models
					Michelin PilotSport PS2	N3	++	++	944 Turbo, '87 - '91 models

0 = satisfactory; + = good;
++ = very good; +++ = excellent

Only tyres of the same make and type, with the same speed index and the same specification code (N0, N1, N2 ...) may be used on a vehicle.

Further detailed information about permitted wheel and tyre sizes as well as spacers that may be required can be found in the relevant parts certificates/manufacturer's certificates held by the Porsche partners.

Recommended makes and types of summer tyres

Type 959									
	Size	RO	Axles	Tyre size	Tread designation	Spec.	Characteristics		Vehicles
							Dry handling	Wet handling	
Wheel size	8Jx17 DL	44	FA	235/45 ZR17	Bridgestone RE 71	NO	+	+	959
17-inch	10Jx17 DL	28.3	RA	255/40 ZR17	Bridgestone RE 71	NO	+	+	

0 = satisfactory; + = good;
 ++ = very good; +++ = excellent

Only tyres of the same make and type, with the same speed index and the same specification code (NO, N1, N2 ...) may be used on a vehicle.

Further detailed information about permitted wheel and tyre sizes as well as spacers that may be required can be found in the relevant parts certificates/manufacture's certificates held by the Porsche partners.

Recommended makes and types of summer tyres

Type 964											
	Size	RO	Axles	Tyre size	Tread designation	Spec.	Characteristics		Vehicles		
Wheel size							Dry handling	Wet handling			
16-inch	6Jx16	52/	FA	205/55 ZR16	Pirelli P-Zero Direzionale	N3	++	++	964 Carrera 2, '90 - '94 models		
					Michelin Pilot Exalto PE2	N0	0	+++	964 Carrera 4, '89 - '94 models		
		Bridgestone Potenza S-02	N3		++	++	964 Carrera RS, '92 model				
		Continental ContiSportContact	N1		+++	+++	964 Speedster, '93 & '94 models				
		Michelin SX MXX3	N2		+	++					
	8Jx16	52/	RA	225/50 ZR16	Pirelli P-Zero Asimmetrico	N3	++	++			
					Michelin Pilot Exalto PE2	N0	0	+++			
		Bridgestone Potenza S-02	N3		++	++					
		Continental ContiSportContact	N1		+++	+++					
		Michelin SX MXX3	N2		+	++					
7Jx16	55	FA	205/55 ZR16	Michelin SX MXX3	N2	+	++	964 Carrera 2, '90 - '94 models			
				Bridgestone Potenza S-02	N3	++	+	964 Carrera 4, '89 - '94 models			
	Continental ContiSportContact	N1		+++	+++	964 Carrera RS, '92 model					
	9Jx16 *)	52,3		RA	245/45 ZR16	Michelin SX MXX3	N2	+	++	964 Speedster, '93 & '94 models	
						Bridgestone Potenza S-02	N3	++	+		
Continental ContiSportContact	N1	+++	+++								
17-inch	7Jx17	55	FA	205/50 ZR17		Pirelli P-Zero Rosso	N3	++	+	964 Carrera 2, '90 - '94 models	
						Bridgestone Potenza S-02A	N4	++	++	964 Carrera 4, '89 - '94 models	
		Continental ContiSportContact2	N2		+++	+++	964 Carrera RS, '92 model				
		Michelin PilotSport PS2	N3		+++	++	964 Speedster, '93 & '94 models				
		8Jx17	52		RA	255/40 ZR17	Pirelli P-Zero Rosso	N3	++	+	
	Bridgestone Potenza S-02A			N4			++	++			
	Continental ContiSportContact2		N2	+++	+++						
	Michelin PilotSport PS2		N3	+++	++						
	7Jx17		55	FA	205/50 ZR17		Pirelli P-Zero Rosso	N3	++	++	964 Carrera 2, '90 - '94 models
		Bridgestone Potenza S-02A				N4	+	+	964 Carrera 4, '89 - '94 models		
Bridgestone Potenza S-02		N3	++	++		964 Carrera RS, '92 model					
Continental ContiSportContact2		N2	++	+++		964 Speedster, '93 & '94 models					
Michelin PilotSport PS2		N3	+++	+++							
9Jx17	55	RA	255/40 ZR17	Pirelli P-Zero Rosso	N3	++	++				
				Bridgestone Potenza S-02A	N4	+	+				
	Bridgestone Potenza S-02	N3		++	++						
	Continental ContiSportContact2	N2		++	+++						
	Michelin PilotSport PS2	N3		+++	+++						
Type 964 Turbo											
	Size	RO	Axles	Tyre size	Tread designation	Spec.	Characteristics		Vehicles		
Wheel size							Dry handling	Wet handling			
17-inch	7Jx17	55	FA	205/50 ZR17	Pirelli P-Zero Rosso	N3	++	++	964 Turbo, '91 & '92 models		
					Bridgestone Potenza S-02A	N4	+	+	964 Turbo S, '92 model		
		Bridgestone Potenza S-02	N3		++	++	964 C2 "Turbo Look", '92 - '93				
		Continental ContiSportContact2	N2		++	+++	964 C4 "Turbo Look", '93 & '94				
		Michelin PilotSport PS2	N3		+++	+++					
	9Jx17	55	RA	255/40 ZR17	Pirelli P-Zero Rosso	N3	++	++			
					Bridgestone Potenza S-02A	N4	+	+			
		Bridgestone Potenza S-02	N3		++	++					
		Continental ContiSportContact2	N2		++	+++					
		Michelin PilotSport PS2	N3		+++	+++					
8Jx17	52	FA	225/45 ZR17	Bridgestone S01	N0	+	+	964 Turbo, '91 & '92 models			
9.5Jx17 *)	68	RA	275/35 ZR17	Bridgestone S01	N0	+	+	964 Turbo S, '92 model			
18-inch	8Jx18	52	FA	225/40 ZR18	Pirelli P-Zero Zero	N4	++	+++	964 Turbo 3.6, '93 & '94 models		
					Bridgestone Potenza S-02A	N3	++	++			
					Continental ContiSportContact2	N2	++	++			
	10Jx18	65/	RA		265/35 ZR18	Michelin PilotSport PS2	N3	++	++		
						Pirelli P-Zero Zero	N4	++	+++		
						Bridgestone Potenza S-02A	N3	++	++		
Continental ContiSportContact2	N2	++	++								
Michelin PilotSport PS2	N3	++	++								

0 = satisfactory; + = good;
++ = very good; +++ = excellent

Only tyres of the same make and type, with the same speed index and the same specification code (N0, N1, N2 ...) may be used on a vehicle.

*) 17-mm spacers on rear axle.

Further detailed information about permitted wheel and tyre sizes as well as spacers that may be required can be found in the relevant parts certificates/manufacturers' certificates held by the Porsche partners.

Recommended makes and types of summer tyres

Type 968									
	Size	RO	Axles	Tyre size	Tread designation	Spec.	Characteristics		Vehicles
Wheel size							Dry handling	Wet handling	
17-inch	7.5Jx17	65	FA	225/45 ZR17	Bridgestone Potenza S-02	N3	+++	+	968, '92 - '95 models
					Michelin PilotSport PS2	N3	++	++	968 CS, '93 - '95 models
	9Jx17	55	RA	255/40 ZR17	Bridgestone Potenza S-02	N3	+++	+	
					Michelin PilotSport PS2	N3	++	++	
Type 968 Turbo S									
	Size	RO	Axles	Tyre size	Tread designation	Spec.	Characteristics		Vehicles
Wheel size							Dry handling	Wet handling	
18-inch	8Jx18	53	FA	235/40 ZR18	Pirelli P-Zero Rosso	N4	++	+++	968 Turbo S, '93 model
					Pirelli P-Zero Rosso	N4	++	+++	

0 = satisfactory; + = good;
++ = very good; +++ = excellent

Only tyres of the same make and type, with the same speed index and the same specification code (N0, N1, N2 ...) may be used on a vehicle.

Further detailed information about permitted wheel and tyre sizes as well as spacers that may be required can be found in the relevant parts certificates/manufacturer's certificates held by the Porsche partners.

Recommended makes and types of summer tyres

Type 993									
	Size	RO	Axles	Tyre size	Tread designation	Spec.	Characteristics		Vehicles
							Dry handling	Wet handling	
Wheel size	7Jx16	55	FA	205/55 ZR16	Michelin SX MXX3	N2	++	++	993 Carrera, '94 - '98 models
16-inch					Continental ContiSportContact	N1	++	++	
	9Jx16	70	RA	245/45 ZR16	Michelin SX MXX3	N2	++	++	
					Continental ContiSportContact	N1	++	++	
Wheel size	7Jx17	55	FA	205/50 ZR17	Pirelli P-Zero Rosso	N3	++	+	993 Carrera, '94 - '98 models
17-inch					Bridgestone Potenza S-02A	N4	++	++	993 Carrera RS, '95 & '96
					Continental ContiSportContact2	N2	++	+++	993 Carrera S, '97 & '98 models
					Michelin PilotSport PS2	N3	++	+	
	9Jx17	55	RA	255/40 ZR17	Pirelli P-Zero Rosso	N3	++	+	
					Bridgestone Potenza S-02A	N4	++	++	
					Continental ContiSportContact2	N2	++	+++	
					Michelin PilotSport PS2	N3	++	+	
Wheel size	8Jx18	50/ 52	FA	225/40 ZR18	Pirelli P-Zero Rosso	N4	++	++	993, '94 - '98 models
18-inch					Bridgestone Potenza S-02A	N3	+	+	993 Carrera RS, '95 & '96
					Continental ContiSportContact2	N2	+	++	not; Targa, Cabriolet before '96
	10Jx18	65	RA	265/35 ZR18	Pirelli P-Zero Rosso	N4	++	++	
					Bridgestone Potenza S-02A	N3	+	+	
					Continental ContiSportContact2	N2	+	++	
Type 993 Turbo									
	Size	RO	Axles	Tyre size	Tread designation	Spec.	Characteristics		Vehicles
							Dry handling	Wet handling	
Wheel size	8Jx18	52	FA	225/40 ZR18	Pirelli P-Zero Rosso	N4	+++	+++	993 Turbo
18-inch					Bridgestone Potenza S-02A	N3	+	++	993 Carrera S
					Continental ContiSportContact2	N2	+++	+++	993 Carrera 4S
					Michelin PilotSport PS2	N3	+++	+	993 Turbo Look
	10Jx18	40/ 65*)	RA	285/30 ZR18	Pirelli P-Zero Rosso	N4	+++	+++	
					Bridgestone Potenza S-02A	N3	+	++	
					Continental ContiSportContact2	N2	+++	+++	
					Michelin PilotSport PS2	N3	+++	+	

0 = satisfactory; + = good;
++ = very good; +++ = excellent

Only tyres of the same make and type, with the same speed index and the same specification code (N0, N1, N2 ...) may be used on a vehicle.

*) with 25-mm spacer on each wheel on rear axle.

Further detailed information about permitted wheel and tyre sizes as well as spacers that may be required can be found in the relevant parts certificates/manufacturer's certificates held by the Porsche partners.